






## PROMAX - Soğutucu Akışkan Geri Toplama Cihazı

	RG 6-E	RG 5410A-E	Minimax-E	RG 3000-E
				
Motor gücü	1HP - 720 Watt	1/2HP - 360 Watt	1/2HP - 360 Watt	1/3HP - 240 Watt
Max çalışma basıncı / Otomatik kesme	38,5 bar	38,5 bar	38,5 bar	38,5 bar
Likid push/pull	456.00 kg/hr	373.20 kg/hr	354.00 kg/hr	229.13 kg/hr
Likid max	211.8 kg/hr	111 kg/hr	90 kg/hr	58,25 kg/hr
Gaz max	15 kg/hr	9.6 kg/hr	9 kg/hr	8.18 kg/hr
Silindir	2	1	1	1
Güç kaynağı	230V 50Hz	230V 50/60Hz	230V 50/60Hz	230V 50Hz
Mevcut olan	115V 50Hz	115V 50/60Hz	115V 50/60Hz	115V 50Hz
IEC bağlantısı	Var	Var	Var	Var
Norm	EN35421	EN35421	EN35421	EN35421
Onay	CE, UL ve ARI	CE, UL, ARI ve TÜV	CE, UL, ARI ve TÜV	CE, UL, ARI ve TÜV
R32 / R1234YF uygunluk	Var	Var	Var	Var
Filtre/Kurutucu	Var	Var	Var	Var
HP Güvenlik anahtarı	Var	Var	Var	Var
LP düğmesi	Var	Var	Yok	Yok
Boyutlar	432x305x228 mm	325x245x485 mm	250x222x406 mm	310x235x175 mm
Ağırlık	14,5 kg	13,5 kg	11 kg	8 kg